



Catalog No	Struck Capacity	Heading Capacity	Mounting Class	Loading/Unloading Angle	Bucket Width (mm)	Bucket Height (mm)	Overall Length	Fork Distance (IT)	Fork Pocket Width (mm)	Fork Pocket Dimensions (mm)	Horizontal Centre of Gravity (mm)	Weight
	m ³	m ³	ISO 2328	°	BW	BH	OL	FD	FPW	FW / FH / FL	HCG	kg
060LMF-X1000	0,5m ³	0,6m ³	Slip on Fork	50° / 50°	1000	864	2550	498	830	145 / 65 / 1200	1342	445
070LMF-X1200	0,6m ³	0,7m ³	Slip on Fork	50° / 50°	1200	880	2550	498	830	145 / 65 / 1200	1364	455
080LMF-X1300	0,7m ³	0,8m ³	Slip on Fork	50° / 50°	1300	880	2550	498	830	145 / 65 / 1200	1386	465
090LMF-X1500	0,8m ³	0,9m ³	Slip on Fork	50° / 50°	1500	900	2550	498	830	150 / 70 / 1200	1485	475
100LMF-X1700	0,9m ³	1,0m ³	Slip on Fork	50° / 50°	1700	900	2550	550	882	150 / 70 / 1200	1490	495
120LMF-X1900	1,0m ³	1,2m ³	Slip on Fork	50° / 50°	1900	950	2550	550	882	170 / 80 / 1500	1495	515
190LMF-X2200	1,5m ³	1,9m ³	Slip on Fork	50° / 50°	2200	1110	3105	550	892	180 / 80 / 1800	1547	600



Technical Information

This attachment is used for loading light materials like Coal, Sand, Seed, etc.

- 1 Hydraulic Function
- Slip-on Fork