



Catalog No	Capacity	Mounting Class	Carriage Width	Opening Range (mm)	Fork Spread (mm)	Fork Dimensions (mm)	Fork Guard Height (mm)	Effective Thickness (mm)	Horizontal Centre of Gravity (mm)	Weight
	kg/mm	ISO 2328	CW	OR	FS / FD	X / Y / Z	AH	ET	HCG	kg
020MPH-A43GJ	2000/500	2A	1220	595-1950	565-695	80 / 40 / 1150	1400	224	243	560
020MPHs-A43GJ	2000/500	2A	1220	595-1950	565-695	80 / 40 / 1150	1400	234	248	578
025MPH-B44GJ	2500/500	2A	1220	595-1950	565-695	80 / 50 / 1150	1400	234	245	585
025MPHs-B44GJ	2500/500	2A	1220	595-1950	565-695	80 / 50 / 1150	1400	240	244	598
028MPH-B45GJ	2800/500	3A	1220	595-1950	565-695	80 / 50 / 1150	1400	234	245	595
028MPHs-B45GJ	2800/500	3A	1220	595-1950	565-695	80 / 50 / 1150	1400	240	244	608
035MPH-B46GJ	3200/500	3A/4A	1220	595-1950	565-695	80 / 60 / 1150	1400	244	248	605
035MPHs-B46GJ	3200/500	3A/4A	1220	595-1950	565-695	80 / 60 / 1150	1400	250	248	618



### Technical Information

- Single or Double Pallet Handling
- 2 Hydraulic Functions
- Quick Release Hooks are optional
- MPH Non-Sideshifting Model
- MPHs Separate Sideshifting Model