


Catalog No	Capacity@ Load Centre	Mounting Class	Opening Range (mm)	Arm Configuration	Pad Size (mm)	Pad Configuration	Effective Thickness (mm)	Horizontal Centre of Gravity (mm)	Weight  kg
	kg/mm	ISO 2328	OR	Short/Long	PW / PL	Qty	ET	HCG	
016PRT-A02HT	1600/600	2A/3A	250-1200	45° Pos. / Positionable	260 / 900	2 Pads	290	224	650
016PRT-A04HP	1600/700	2A/3A	250-1400	45° Pos. / Positionable	260 / 900	2 Pads	290	327	655
016PRT-B05HS	1600/750	2A/3A	250-1500	45° Pos. / Positionable	260 / 900	2 Pads	290	330	660
016PRC-B06HZ	1600/800	2A/3A	250-1600	45° Pos. / Positionable	260 / 900	2 Pads	290	333	687
020PRT-A02HT	2000/600	2A/3A	250-1200	45° Pos. / Positionable	260 / 900	2 Pads	290	325	760
020PRT-A04HP	2000/700	2A/3A	250-1400	45° Pos. / Positionable	260 / 900	2 Pads	290	326	770
020PRT-B05HS	2000/750	2A/3A	250-1500	45° Pos. / Positionable	260 / 900	2 Pads	290	375	790
020PRT-B06HZ	2000/800	2A/3A	250-1600	45° Pos. / Positionable	260 / 900	2 Pads	290	379	800
026PRT-B05HS	2600/750	3A	250-1500	45° Pos. / Positionable	300 / 1000	2 Pads	290	364	880
026PRT-B06HZ	2600/800	3A	250-1600	45° Pos. / Positionable	300 / 1000	2 Pads	290	365	890
026PRT-B08HY	2600/900	3A	250-1800	45° Pos. / Positionable	300 / 1000	2 Pads	290	370	900
026PRT-B09HJ	2600/950	3A	250-1900	45° Pos. / Positionable	300 / 1000	2 Pads	290	373	910
030PRT-B05HS	3000/750	3A/4A	250-1500	45° Pos. / Positionable	300 / 1100	2 Pads	261	355	1200
030PRT-B06HZ	3000/800	3A/4A	250-1600	45° Pos. / Positionable	300 / 1100	2 Pads	261	358	1220
030PRT-B08HY	3000/800	3A/4A	250-1800	45° Pos. / Positionable	300 / 1100	2 Pads	261	360	1230
030PRT-B09HJ	3000/950	3A/4A	250-1900	45° Pos. / Positionable	300 / 1100	2 Pads	261	362	1240
030PRT-B10HG	3000/1000	3A/4A	400-2000	45° Pos. / Positionable	300 / 1100	2 Pads	261	365	1250
035PRT-B05HS	3500/750	4A	250-1500	45° Pos. / Positionable	350 / 1200	2 Pads	261	358	1245
035PRT-B06HZ	3500/800	4A	250-1600	45° Pos. / Positionable	350 / 1200	2 Pads	261	360	1255
035PRT-B08HY	3500/900	4A	250-1800	45° Pos. / Positionable	350 / 1200	2 Pads	261	363	1265
035PRT-B09HJ	3500/950	4A	250-1900	45° Pos. / Positionable	350 / 1200	2 Pads	261	365	1275
035PRT-B10HG	3500/900	4A	400-2000	45° Pos. / Positionable	350 / 1200	2 Pads	261	369	1285



#### Technical Information

- Attachment rotates hydraulically by 360° endless in both directions.
- 2 hydraulic functions
- Different contact pad coatings are available.
- 45° Short Arm Movement
- Wide surface contact pads for Tissue Rolls